ALSAFIX®

TECHNICAL SPECIFICATIONS

20/64 B2

Cordless brad nailer

Cordless brad nailer, ideal for carpentry, fitting out, fixing stairs or even parquet flooring.



L 286 l 96 H 289	2,32 kg	2,5 Ah Li-ion 18 V	✓	110	32 - 64 mm	1,60 mm

20/64 B2 | TECHNICAL SPECIFICATIONS

Batteray-powered brad nailer

Code **12B2064B2**



Description

Cordless brad nailer, ideal for carpentry, fitting out, fixing staircases or even parquet flooring.


Dimensions (L/l/H) (mm)	286 / 96 / 289 mm
Weight (kg)	2,32 kg
Firing	Single shot / Burst
Magazine capacity	110 nails
Projectile type	Brads 20°
Projectile lenght (mm)	32 - 64 mm
Projectile diameter	1,60 mm
Firing rate	up to 3 to 4 shots /second
Maximum shots per charge	1 050 shots/charge
Battery type	Li-ion 18 V - 2.5 Ah
EAN code	3660601092476
Supplied with	Case, 2 batteries and 1 charger

Projectile

Brads 20°

32 - 64 mm

ø 1.60



G A2

Other version available

› **code : 12B2064X** - Supplied without case, battery or charger

Advantages

- Supplied in a case with 2 batteries and 1 charger
- Powerful brushless motor, 30 J
- Quick release nose, no tools required
- 6 levels of electronic depth adjustment
- Up to 1,050 shots per battery charge
- Compact design and perfect balance
- Thin nose for more precise nailing
- Non-slip handle
- Compatible with 2.5 and 5 Ah batteries from the range

Noise level and vibrations

Characteristic noise values in accordance with the standard	**EN 12549+A1**
A-weighted sound pressure level at the workstation	**73,4 dB**
A-weighted sound power level	**84,4 dB**
C-weighted instantaneous peak sound pressure level at the workstation	**76,4 dB**
Vibration value according to EN ISO 28927-13	**2,42 m/s²**

Related products

Battery
18 V - **2.5 Ah**
code :
12BAT1825



Battery
18 V - **5.0 Ah**
code :
12BAT1850



Charger
18 V
code :
12CHRG18



ALSAFIX reserves the right to modify certain technical characteristics. Information provided for informational purposes only.
Alsafix cannot be held liable in the event of implementation without prior calculations and tests specifc to each case. Presentation photos are not contractual.

114a rue Principale
FR 67240 GRIES
Tél. +33 3 88 72 19 31
alsafix@alsafix.com
www.alsafix.com