

# CCABB 131

## Cordless drill/drivers and impact wrenches

Ultra-compact cordless impact drill/driver (110 mm), perfectly suited to all your building and industrial work: electrical, masonry, carpentry, cabinet making, plumbing, and much more.





**ALSAFIX** 



L 110 I 62 H 208



0,88 kg



5,0 Ah Li-ion 18 V







1/4" - Hex



224 Nm



#### SCREW > CORDLESS DRILL/DRIVERS AND IMPACT WRENCHES

#### **CCA-B1** | TECHNICAL SPECIFICATIONS

Cordless drill/drivers and impact wrenches

Code 12CC1850

#### **Description**

Very compact cordless impact wrench (110 mm), ideal for all your building and industrial work. Electrical installations, masonry, carpentry, cabinet making, plumbing, etc.

Dimensions (L/I/H) (mm)	110 / 62,5 / 208 mm	
Weight (kg)	0,88 kg (tool only)	
Socket	6 pans - 1/4"	
Max. torque	224 Nm	
No-load speed	Low speed : 0 - 1 100 rpm Average speed : 0 - 2 900 rpm High speed : 0 - 3 600 rpm	
Impacts	Low speed : 0 - 1 100 imp/min Average speed : 0 - 3 500 imp/min High speed : 0 - 3 800 imp/min	
Modes	Screwing/bolting	
EAN code	3660601092599	
Supplied with	Case, 2 batteries and 1 charger	



Screwdriving	Max. recommended
Wood screws	М8
Bolting	
Bolts	M16
High-strength bolts	M14

### Related products

Battery	Battery	Charger
18 V - <b>2.5 Áh</b>	18 V - <b>5.0 Åh</b>	18 V
code :	code :	code :
12BAT1825	12BAT1850	12CHRG18









#### **Advantages**

- > Supplied in a case with 2 batteries and 1 charger
- > Special bolting mode with automatic speed reduction at the end of the stroke
- > Special screwdriving mode with turbo speed for difficult jobs
- > Progressive trigger for increased speed control
- > LED lighting for the work area
- > High-performance brushless motor delivering up to 224 Nm of torque
- > Rotation direction selector
- > Compatible with 2.5 and 5.0 Ah batteries in the range

#### Noise level and vibrations

Noise characteristics in accordance with standard	EN 12549+A1
A-weighted sound pressure level at the workstation (impact)	92.7 dB
A-weighted sound power level (impact)	103.7 dB
Vibration value according to EN ISO 28927-13	14.5 m/s <sup>2</sup>

#### Other versions available

> code: 12CC1825 - Supplied in a case with 2 x 18 V - 2.5 Ah L-ion batteries and 1 charger

> code : 12CC180X - Supplied without case, battery or charger

ALSAFIX reserves the right to modify certain technical characteristics. Information provided for guidance only. Alsafix cannot be held liable in the event of implementation without prior calculations and tests specific to each case. Presentation photos are not contractually binding







