ALSAFIX®

TECHNICAL SPECIFICATIONS

CCA-B1

Cordless drill/drivers and impact wrenches

Ultra-compact cordless impact drill/driver (110 mm), perfectly suited to all your building and industrial work: electrical, masonry, carpentry, cabinet making, plumbing, and much more.



L 110 l 62 H 208	0,88 kg	5,0 Ah Li-ion 18 V	✓	1/4" - Hex	224 Nm

CCA-B1 | TECHNICAL SPECIFICATIONS

Cordless drill/drivers and impact wrenches

Code **12CC1850**



Description

Very compact cordless impact wrench (110 mm), ideal for all your building and industrial work. Electrical installations, masonry, carpentry, cabinet making, plumbing, etc.

Dimensions (L/l/H) (mm)	110 / 62,5 / 208 mm
Weight (kg)	0,88 kg (tool only)
Socket	6 pans - 1/4"
Max. torque	224 Nm
No-load speed	Low speed : 0 - 1 100 rpm Average speed : 0 - 2 900 rpm High speed : 0 - 3 600 rpm
Impacts	Low speed : 0 - 1 100 imp/min Average speed : 0 - 3 500 imp/min High speed : 0 - 3 800 imp/min
Modes	Screwing/bolting
EAN code	3660601092599
Supplied with	Case, 2 batteries and 1 charger

Advantages

- Supplied in a case with 2 batteries and 1 charger
- Special bolting mode with automatic speed reduction at the end of the stroke
- Special screwdriving mode with turbo speed for difficult jobs
- Progressive trigger for increased speed control
- LED lighting for the work area
- High-performance brushless motor delivering up to 224 Nm of torque
- Rotation direction selector
- Compatible with 2.5 and 5.0 Ah batteries in the range

Capacities

Screwdriving	**Max. recommended**
Wood screws	**M8**
Bolting	
Bolts	**M16**
High-strength bolts	**M14**

Noise level and vibrations

Noise characteristics in accordance with standard	**EN 12549+A1**
A-weighted sound pressure level at the workstation (impact)	**92.7 dB**
A-weighted sound power level (impact)	**103.7 dB**
Vibration value according to EN ISO 28927-13	**14.5 m/s²**

Related products

Battery
18 V - **2.5 Ah**
code :
12BAT1825



Battery
18 V - **5.0 Ah**
code :
12BAT1850



Charger
18 V
code :
12CHRG18



Other versions available

- **code : 12CC1825** - Supplied in a case with 2 x 18 V - 2.5 Ah L-ion batteries and 1 charger
- **code : 12CC180X** - Supplied without case, battery or charger

ALSAFIX reserves the right to modify certain technical characteristics. Information provided for informational purposes only.
Alsafix cannot be held liable in the event of implementation without prior calculations and tests specifc to each case. Presentation photos are not contractual.

114a rue Principale
FR 67240 GRIES
Tél. +33 3 88 72 19 31
alsafix@alsafix.com
www.alsafix.com