

# Pressure regulator

**Technical description** 

Code R040-01 Version 1/4"

Code R050-01 3/8" Version

Weight 350 gr **Operating temperature** 

#### 5°C - 60°C **Operating pressure** 0 - 10 bars

#### **Benefits**

- Can be mounted directly on a compressed air
- Pressure gauge graduated from 0 to 10 bars.
- With 1/4" and 3/8" threads depending on the model.
- Supplied with mounting bracket.















# Pressure regulating filter

## **Technical description**

Code FR040-04

Version 1/4"

Code FR050-14

3/8" Version

Weight 350 gr **Operating temperature** 5°C - 60°C **Operating pressure** 0 - 10 bars

## **Benefits**

- Can be mounted directly on a compressed air network.
- Pressure gauge graduated from 0 to 10 bars.
- With 1/4" and 3/8" threads depending on the model.
- Filtration from 5 to 40  $\mu$ .
- Supplied with mounting bracket.













## Technical description

Code L040-03

Version 1/4"

Code L040-13 **Version** 3/8"

Weight 350 gr **Operating temperature** 5°C - 60°C **Operating pressure** 0 - 10 bars

#### **Benefits**

- Can be mounted directly on a compressed air network.
- With 1/4" and 3/8" threads depending on the model.
- Can be used from 5 to 60°C with HUILEVAS1L pneumatic oil.
- Oil bowl capacity: 7.5 cl.















## **Technical description**

Code FR+L1/4 Version 1/4"

Code FR+L3/8 3/8" **Version** 

Weight 980 gr **Operating temperature** 5°C - 60°C **Operating pressure** 0 - 10 bars

#### **Benefits**

- Can be mounted directly on a compressed air network.

filter + lubricator

- Pressure gauge graduated from 0 to 10 bars.
- With 1/4" and 3/8" threads depending on the model.
- Usable from 5 to 60°C with HUILEVAS1L pneumatic oil.
- Filtration from 5 to 40  $\mu$ .
- Oil bowl capacity: 7,5 cl.











