

suprabeam®

Q7 *xrs*

ALSAFIX®
www.alsafix.com

Powerful Light - 4200 Lumens

Longer Runtimes and Brighter
Light with Advanced DC Converter
Technology

Versatile use with
Sliding Hyperfocus™
and Focuslock



4200 LUMENS



Li-ion
5000 mAh



440 m



297 g



15° - 75°

SB5076311

PACKAGING



Customs Tariff Number:	8513 1000
Packaging:	Recyclable Cardboard Packaging
Single Box Content / Size / Weight:	1 pcs, height/width/depth: 19 x 19 x 5 cm / 527 g
Master Box Content / Size / Weight:	5 pcs, height/width/depth: 22 x 28 x 21 cm / 2.9 kg
Code:	SB5076311
CODE EAN:	5704049911543

SPECIFICATIONS

LED / Focus Configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Prime Aluminium quality 6061, anodized
Case Color:	Anthracite Dark Grey
Switch at Rear:	Electronic Switch with Solid Silicone Button
Dimensions:	L: 158 mm, ø: 46 mm
Weight incl. Battery:	297 g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature (Operation):	-20°C to +50°C

ELECTRONICS

Built in Controller:	Yes, DIM and STEP mode
Standard Power Source:	Li-ion 26650 (5000 mAh)
Charging Time:	80% = 3 h, 100% = 4 h 30 min
Beam / Distance:	Variable from Spot to Floodlight / 440 Meters
Luminous Flux:	Max: 4200 lm, Dimmable: 1000 lm -6 lm
Lighting Time:	Max: 2 h / High dim: 2 h 45 min / Low dim: 600 h
Accessories Included:	Holster, Strap, USB-C cable and external ICR 26650 Charger
Charging Temperature:	-0°C to +45°C

Distributed by:



ALSAFIX HEAD OFFICE
114A rue Principale
FR-67240 GRIES
Tel: +33 3 88 72 19 31

ALSAFIX PARIS
34 avenue de Bobigny
FR-93135 NOISY-LE-SEC
Tel: +33 1 48 44 44 59

www.alsafix.com
alsafix@alsafix.com

www.alsafix.com
paris@alsafix.com